

No one does it like you

Canon

# EXPECT QUALITY WITH SEAMLESS PERFORMANCE

The imageRUNNER ADVANCE DX C7700i Series provides you with transparency and control – putting you in the driver's seat and allowing you to manage projects with ease in the office or on the go. Expect consistent, quality output with advanced printing and finishing capabilities.

## Canon imageRUNNER ADVANCE DX C7700i Performance Series



### MOBILITY

#### Connect on-the-go

- Simple and easy mobile connectivity with in-built WiFi plus options to connect through Bluetooth and Near Field Communication (NFC).
- Give your team flexibility so projects don't need to stop just because they are away from the office.
- Intuitive printing and scanning using Canon PRINT Business plus built in support for Apple® AirPrint®, Mopria™ and Google Cloud™.

### SECURITY

#### Protect sensitive information with enhanced security capabilities

- Advanced control over document access ensures documents are only seen by those that are authorised.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialise without alterations or tampering time and money spent on various projects.

### COST CONTROL

#### Advanced functions for big cost-saving

- Save your business money by reducing your paper wastage utilising settings such as forced job hold at the device, and blank page removal.
- Enable print policies to monitor output while also restricting users from overuse.
- Save even further with remote support to help diagnose and solve issues fast, rather than taking up the valuable time of in-house IT staff.
- Track usage and control your costs utilising Canon's uniFLOW Online Express free software.

### PERFORMANCE

#### Designed for a simple, tailored experience

- The large interface allows for easy navigation while My ADVANCE provides a personalised experience so you can customise your workflow in a way that works best for you.
- Video guidance to help with basic maintenance.
- Speed up processes with the single pass document feeder and automatic blank page removal.
- Achieve outstanding results with V2 imaging technology (V2 colour and true 2400 dpi) and a range of finishing options including stapling, booklet, staple on-demand and eco staple.

### INTEGRATION

#### Systems seamlessly converge for smooth operation and easy handling

- Canon's MEAP platform works to integrate both new and existing document, capture and output management systems while being partnered with relevant support technology.
- Collaborate with key line of business applications and external systems.
- For smooth, hassle-free projects, scan and convert to Microsoft® Word and PowerPoint® files.
- Supports integration with popular cloud services like Google Drive™ and Box\*\*.

### SUSTAINABILITY

#### Environmentally conscious technology works to achieve green initiatives for your business

- The imageRUNNER ADVANCE DX C7700i runs efficiently to help eliminate unnecessary power consumption and is designed to reduce emissions.
- Motion sensors, sleep recovery triggers, 100% recycled plastics, and remote shutdown are all features that contribute to ongoing sustainability.
- Minimise paper wastage with default print settings including double-sided print and black and white.
- ENERGY STAR® and Blue Angel qualified with class leading Typical Electricity Consumption (TEC) rating.

\*\* Requires uniFLOW Online Express or uniFLOW Online subscription.

# DEVICE SECURITY

The imageRUNNER ADVANCE DX C7700i Series feature the ability to help verify that the device boot process, firmware and applications initialise at startup, without any alterations or tampering by malicious third parties.

During operation, McAfee Embedded Control™ utilises a whitelist to protect against malware and tampering of firmware and applications.\*\*



\*\* These features are available on third generation imageRUNNER ADVANCE Gen III Series III or imageRUNNER ADVANCE DX models only. McAfee Embedded Control™ requires Unified Firmware Platform v3.9 or above.

# CONFIGURATION

## Staple Finisher

- 3-tray, 3,500-sheet capacity (A4, B5, A5R)  
1,750-sheet capacity (A3, B4, A4R, B5R)
- Corner and double stapling up to 65 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand 65 sheets (80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers



## Booklet Finisher

- 3-tray, 3,500-sheet capacity (A4, B5, A5R)  
1,750-sheet capacity (A3, B4, A4R, B5R)
- Corner and double stapling up to 65 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 5 sheets
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand 65 sheets (80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers



## Document Insertion Unit

- Insert preprinted sheets
- Up to A3
- One tray
- 100-sheet total



## Document Insertion / Folding Unit

- Insert, C-fold and Z-fold preprinted sheets
- Up to A3
- One tray
- 100-sheet total



Upright Control Panel



Utility Tray



Copy Tray



## imagePASS-N2

- PS3/PCL6
- 4 GB/500 GB
- Fiery FS350

## Paper Deck Unit (A4)

- Supports A4, B5
- Media Weight 52 to 256 gsm
- 3,500 sheets (80 gsm)



## Paper Deck Unit (A3)

- Supports A3, B4, A4 A4R, B5R, B5, A5R, SRA3, 13" x 19"
- Media Weight 52 to 256 gsm
- 3,500 sheets (80 gsm)



# imageRUNNER ADVANCE DX C7700i Performance Series SPECIFICATIONS



Main Unit	
Type	A3 Colour Laser Multifunctional
Core Function	Print, Copy, Scan, Send, Store and Optional Fax
Processor	1.75 GHz Dual Core Processor
Control Panel	Standard: 10.1 inch TFT LCD WSVGA Colour Touch Panel Optional: 10.4 inch TFT LCD SVGA Colour Upright Touch Panel
Memory	Standard: 4 GB RAM
Hard Disk Drive	Standard*: 320 GB (available disk space: 250 GB) Optional: 250 GB, 1 TB * A different initial HDD may be used.
Mirroring Hard Disk Drive	Optional
Interface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy Standard: USB 2.0 (Host) x 2, USB 3.0 (Host) x 1, USB 2.0 (Device) x 1 Optional: Serial Interface, Copy Control Interface
Paper Capacity (80gsm)	Standard: 3,550 Sheets 250-sheet Multi-purpose Tray x 1 1,100-sheet Paper Deck x 2 550-sheet Paper Cassette x 2 Maximum: 6,800 Sheets
Paper Output Capacity (A4, 80 gsm)	250 Sheets (with Copy Tray-R2) Maximum: 3,500 Sheets (with Staple Finisher-AC1 or Booklet Finisher-AC1)
Finishing Capabilities	With options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On-demand, Document Insertion, Z-fold, Half-fold, C-fold, Accordion-Z fold, Double Parallel-fold, Trimming
Supported Media Types	Multi-purpose Tray: Thin, Plain, Recycled, Colour, Heavy, Coated, Textured, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope Paper Deck (Right/Left): Thin, Plain, Recycled, Colour, Heavy, Tracing, Bond, Transparency, Bond, Pre-punched, Letterhead Paper Cassettes (Upper/Lower): Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Tab*, Envelope* *1 Tab Feeding Attachment-F1 is required. *2 Envelope Feeder Attachment-F1 is required.
Supported Media Sizes	Multi-purpose Tray: Standard Size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 100.0 x 148.0 mm to 330.2 x 487.7 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Envelope Custom Size: 98.0 x 148 mm to 330.2 x 487.7 mm Paper Decks (Right/Left): Standard Size: A4, B5 Paper Cassettes (Upper/Lower): Standard Size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 139.7 x 182.0 mm to 330.2 x 487.7 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Envelope Custom Size: 98.0 x 148.0 mm to 330.2 x 487.7 mm
Supported Media Weights	Multi-purpose Tray: 52 to 300 gsm Paper Deck (Right/Left): 52 to 220 gsm Paper Cassette (Upper/Lower): 52 to 256 gsm Duplex: 52 to 220 gsm
Warm-up Time	Quick startup mode: 4 seconds or less* * Time from device power on to when the copy icon appears and is enabled to operate on the touch panel display. From Sleep Mode: 30 seconds or less From Power On: 30 seconds or less* * Time from device power-on, until copy ready (not print reservation).
Dimensions (W x D x H)	689 x 937 x 1185 mm
Installation Space (W x D)	Basic: 1740 x 1,524 mm (with Front door open + Multi-purpose Tray/Upper-right cover open + Buffer Pass-M1 + Booklet Finisher-AC1/extension tray + rotary tray extended) Fully Configured: 2,621 x 1,524 mm (with POD Deck Lite-C1 + Buffer Pass-M1 + Document Insertion Unit-Q1 + Booklet Finisher-AC1/extension tray extended)
Weight	Approx. 257 kg (including toner)
Print Specifications	
Printing Method	Colour Laser Beam Printing
Print Speed (BW/CL)	IR-ADV DX C7780i: Up to 80/70 ppm (A4, A5*, A5R, A6R*), Up to 40/35 ppm (A3), Up to 56/49 ppm (A4R) IR-ADV DX C7770i: Up to 70/65 ppm (A4, A5*, A5R, A6R*), Up to 35/32 ppm (A3), Up to 49/46 ppm (A4R) IR-ADV DX C7765i: Up to 65/60 ppm (A4, A5*, A5R, A6R*), Up to 32/30 ppm (A3), Up to 46/42 ppm (A4R) * A5/A6R (1-sided)
Print Resolution	2,400 x 2,400 dpi
Page Description Languages	Standard: UFR II, PCL6 Optional: Adobe® PostScript® 3*
Direct Print	Supported File Types: PDF, EPS, TIFF/JPEG and XPS
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap Fonts, 2 OCR Fonts, Andalé Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode Fonts*2 *1 Optional PCL International Font Set-A1 is required. *2 Optional Barcode Printing Kit-D1 is required.
Printing from Mobile and Cloud	AirPrint®, Mopria™, Google Cloud Print™, Canon Business PRINT, and uniFLOW Online. A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Operating System	UFR II: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, Mac OS X (10.10 or later) PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019 PS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, Mac OS X (10.10 or later) PPD: Windows® 7/8.1/10, Mac OS X (10.9 or later)
Print Features	Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold Printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
Copy Specifications	
Copy Speed (BW/Colour)	IR-ADV DX C7780i: Up to 80/70 ppm (A4, A5*, A5R, A6R*), Up to 40/35 ppm (A3), Up to 56/49 ppm (A4R) IR-ADV DX C7770i: Up to 70/65 ppm (A4, A5*, A5R, A6R*), Up to 35/32 ppm (A3), Up to 49/46 ppm (A4R) IR-ADV DX C7765i: Up to 65/60 ppm (A4, A5*, A5R, A6R*), Up to 32/30 ppm (A3), Up to 46/42 ppm (A4R) * A5/A6R (1-sided)
First-Copy-Out Time (A4)	IR-ADV DX C7780i: Approx. 4.4/5.4 seconds or less IR-ADV DX C7770i: Approx. 4.8/5.9 seconds or less IR-ADV DX C7765i: Approx. 4.8/5.9 seconds or less
Copy Resolution	600 x 600 dpi
Multiple Copies	Up to 9,999 Copies
Copy Exposure	Automatic or Manual (9 Levels)
Magnification	Variable Zoom: 25% to 400% (1% Increments) Preset Reduction/Enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%

Copy Features	Preset R/E Ratios by Area, Two-sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Mirror Image, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Free Size Original, Colour Mode, Reserved Copy, Copy Sample
Scan Specifications	
Type	Single Pass Duplexing Automatic Document Feeder* (2-sided to 2-sided (Automatic)) * Feeder Multi Sheet Feed is supported.
Document Feeder Paper Capacity (80 gsm)	Up to 200 Sheets
Acceptable Originals and Weights	Platen: Sheet, Book, and 3-Dimensional objects Document Feeder Media Weight: 1-sided scanning: 38 to 220 gsm (BW, CL) 2-sided scanning: 38 to 220 gsm (BW, CL) * An acceptable weights of A6R or smaller is 50 to 220gsm.
Supported Media Sizes	Platen Max. Scanning Size: Up to 297.0 x 431.8 mm Document Feeder Media Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R, Custom Size: 70.0 x 139.7 mm to 304.8 x 431.8 mm
Scan Speed (ipm: BW/CL; A4)	1-sided Scanning: 135/135 (800 x 300 dpi, Send), 80/80 (600 x 600 dpi, Copy), 2-sided Scanning: 270/270 (300 x 300 dpi, Send), 160/90 (600 x 600 dpi, Copy)
Scan Resolution (dpi)	Scan for Copy: 600 x 600 Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600 Scan for Fax: 600 x 600
Pull Scan Specifications	Colour Network ScanGear2. For both TWAIN and WIA. Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016
Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Box, Scan to Network, Scan to USB Memory Key, Scan to Mobile Device, Scan to Cloud (uniFLOW Online)
Send Specifications	
Destination	Standard: E-mail/Internet FAX (SMTP) SMB3.0 FTP WebDAV Mail Box Optional: Super G3 FAX, IP Fax
Address Book	LDAP (2,000/Local (1,600)/Speed dial (200)
Send Resolution (dpi)	Push: Up to 600 x 600 Pull: Up to 600 x 600
Communication Protocol	File: FTP (TCP/IP), SMB3.0 (TCP/IP), WebDAV E-mail/Fax: SMTP, POP3
File Format	Standard: TIFF, JPEG, PDF (Limited Colour, Compact, Searchable, Apply Policy, Optimise for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages
Fax Specifications	
Maximum Number of Connection Lines	4
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Receiving Size	Sending: A3, A4, A4R, A5*, A5R*, B4, B5*, B5R* Receiving: A3, A4, A4R, A5R, B4, B5, B5R *1 Sent as A4 *2 Sent as B4 short
Fax Memory	Up to 30,000 Pages (2,000 Jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log
Store Specifications	
Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inboxes, 50 Confidential Fax Inboxes Maximum 10,000 Pages (2,000 jobs) Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 8.1/10 Concurrent Connections (Max.): SMB: 64, WebDAV: 3
Advanced Box Available Disc Space	Standard: 16 GB (With option: max. 480 GB)
Advanced Box Features	Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to Public, URI TX, Backup/Restore
Security Specifications	
Authentication and Access Control	Standard: User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Device Security	Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated)), HDD Data Overwrite Erase, HDD Lock, Standard HDD Initialise, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection)
Network Security	TLS 1.3, IPsec, IEEE802.1X Authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX Separation from LAN, USB Port Separation from LAN, Prohibit the Execution of Files Stored in Advanced Box in the MFP, Scan and Send-virus Concerns for E-mail Reception
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print™), Receive Data Security (Confidential Fax Inboxes Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX Number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) *1 Requires uniFLOW Online/uniFLOW
Device Management and Auditing	Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting
Environmental Specifications	



Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity)
Power Requirements	IR-ADV DX C7780i: 220–240V 50/60Hz 15A IR-ADV DX C7770i/IR-ADV DX C7765i: 220–240V 50/60Hz 10A
Power Consumption	Maximum: Approx. IR-ADV DX C7780i: 2,500 W, IR-ADV DX C7770i/C7765i: 2,000 W Standby: Approx. 119.6 W*1 Sleep Mode: Approx. 0.9 W*2 *1 Reference Value: Measured One Unit *2 0.9 W Sleep mode is not available in all circumstances due to certain settings.

#### Consumables

Toner	NPG-72 Toner BK/C/M/Y
Toner Yield (Estimated @ 5% Coverage)	NPG-72 Toner BK: 82,000 Pages NPG-72 Toner C/M/Y: 66,500 Pages

#### Software and Printer Management

Remote Management Tools	eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance). Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.
Scanning Software	Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.
Optimisation Tools	Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers (Available via service only). NetSpot Device Installer: Simple utility software that allows you to make network protocol settings for Canon devices connected to your network.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services.

#### Fiery Print Controller Specifications

Optional/Standard	Optional
Name	imagePASS-N2 V11 (Embedded)
Print Resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi
Page Description Languages	Adobe PS3, PCL6
Memory	4 GB (1 x 4 GB)
Hard Disk Drive	500 GB SATA
Processor	Intel Pentium G4400 (3.3 GHz)
System	FS350
Fonts	PS: 138 Fonts PCL: 113 Fonts
Supported Operating Systems	Windows® 7 64 bit/Windows® 8.1 64 bit/Windows® 10 64 bit/Windows® Server 2008 R2 64 bit only/Windows® Server 2012 64 bit only (Only Printer Driver Support)/Windows® Server 2012 R2 64 bit only/Windows® Server 2016 R2 64 bit only/Mac OS (10.11, 10.12, 10.13, 10.14)
Interface	2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 2 (Rear), USB2.0 x 4 (Rear)
Network Protocols	TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNTIP, 802.1X, DHCP, DNS, NTP)
Direct Print	PDF1.7, EPS, TIFF6, JDF1.4/JMF (Optional)
VDP	FreeForm v1, v2.1
Fiery Print Controller Standard Features	Fiery Command WorkStation 6/Paper Catalogue/Fiery Spot-on/Fiery Remote Scan/Fiery Hot Folders & Virtual Printers
Fiery Print Controller Options	Fiery Impose/Fiery Compose/Fiery Impose and Compose/Productivity Package Web Activate (Include Fiery JDF)
HW Platform	E400
Base OS	Debian of Linux
Maximum Power Consumption	47 W
Dimensions (W x D x H)	285 x 93 x 295 mm
Weight	Fiery Unit Only (with plate) Approx. 5 kg

#### Paper Supply Options

Paper Deck Unit-E1	Paper Capacity: 3,500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Colour, Heavy, Bond, Pre-punched, Letterhead Paper Size: A4, B5 Paper Weight: 52 to 256 gsm Power Source: from the Main Unit Dimensions (W x D x H): 340 x 630 x 572 mm (attached to the main unit) Weight: Approx. 34 kg
POD Deck Lite-C1	Paper Capacity: 3,500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Colour, Heavy, Coated, Textured, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope* Paper Size: SRA3, A3, B4, A4, A4R, A5R, B5, B5R, Envelope (COM10 No.10, Monarch, DL, ISO-C5), Custom size: 139.7 x 148.0 mm to 330.2 to 487.7 mm Paper Weight: 52 to 300 gsm Power Source: 220–240V/1.2A 50/60Hz Dimensions (W x D x H): 633 x 686 x 574 mm (attached to the main unit) Weight: Approx. 68 kg * Envelope Feeder Attachment-G1s required.

#### Output Options

Copy Tray-R2	Provides a simple tray for basic output needs. Capacity: 250/100 sheets (1-sided/2-sided, 80 gsm) Dimensions (W x D x H): 420 x 382 x 175 mm
Staple Finisher-AC1	Tray Capacity (with 80 gsm paper): Upper Tray: A4, A5, A5R, A6R, B5: Up to 250 Sheets SRA3, A3, A4R, B4, B5R: Up to 125 Sheets Envelope: 30 Sheets Mid Tray: Same as Upper Tray Lower Tray: A4, A5, A5R, B5: 3,000 Sheets SRA3, A3, A4R, B4, B5R: 1,500 Sheets A6R: 250 Sheets Envelope: Monarch: 30 Sheets, COM10 No.10, DL, ISO-C5: 100 Sheets Paper Weight: Upper Tray: 52 to 256 gsm Mid Tray: 52 to 256 gsm Lower Tray: 52 to 300 gsm Staple Position: Corner, Double Staple Capacity (including Staple On-demand): A4/B5: 65 Sheets (52 to 90 gsm) A3/A4R/B4: 40 Sheets (52 to 90 gsm) Eco Staple: A3/A4: 5 Sheets (52 to 64 gsm) 4 Sheets (65 to 81.4 gsm) 3 Sheets (82 to 105 gsm) Staple On-demand: 65 Sheets (90 gsm) Power Supply: From Main Unit Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended) Weight: Approx. 36 kg
Booklet Finisher-AC1	(Includes the above Staple Finisher-AC1 basic staple specifications.) Saddle Stitch Paper Size: A3, A4R, B4, Custom Size (195.0 x 270.0 mm to 330.2 x 457.2 mm) Saddle Stitch Staple Capacity: 20 sheets x 10 sets (52 to 81.4 gsm) (including 1 cover sheet up to 256 gsm)
Document Insertion Unit-Q1	(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1) Number of trays: 1 Tray Capacity: Up to 100 Sheets (80 gsm) Acceptable Paper Type: Thin, Plain, Recycled, Colour, Heavy, Coated, Textured, Bond, Letterhead, Tab Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R Acceptable Paper Weight: 60 to 256 gsm Power Source: 100–240V/50/60Hz 1.0A Dimensions (W x D x H): 247 x 679 x 1,242 mm (attached to the device: width excluding document tray) Weight: Approx. 40 kg
Document Insertion/Folding Unit-K1	(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1) Number of trays: 1 Tray Capacity: Insertion: Up to 100 Sheets (80 gsm) Z-Fold: 11" x 17": Up to 30 Sheets (80 gsm) C-Fold: Up to 40 Sheets (80 gsm) Supported Folding Type: Z-Fold, C-Fold Acceptable Paper Type: Insertion Unit: Thin, Plain, Recycled, Colour, Heavy, Coated, Textured, Bond, Letterhead, Tab Z-Fold/C-Fold: Thin, Plain, Recycled, Colour Acceptable Paper Sizes: Insertion Unit: SRA3, A3, A4, A4R, B4, B5, B5R Z-Fold: A3, A4R, B4 C-Fold: A4R Acceptable Paper Weight: Insertion Unit: 60 to 256 gsm Z-Fold/C-Fold: 60 to 105 gsm Power Source: 100–240V/50/60Hz 1.0A Dimensions (W x D x H): 247 x 679 x 1,242 mm (attached to the device: width excluding document tray) Weight: Approx. 76 kg

#### Hardware Accessories

Others	Tab Feeding Attachment Kit-F1, Utility Tray-B1, Envelope Feeder Attachment-G1, Envelope Feeder Attachment-F1, Upright Control Panel-J1, Numeric Keypad, Finisher Jogger Kit
--------	---

#### Security Options

Data Security	HDD Mirroring Kit-J1, 2.5 inch/250 GB HDD-N1, 2.5 inch/1TB HDD-P1
---------------	---

#### System and Controller Options

Print Accessories	PCL International Font Set-A1, PS Printer Kit-BF1
Barcode Printing	Barcode Printing Kit-D1
EFI-Fiery Based Controller	imagePASS-N2 V11
EFI-Fiery Based Controller Options	Fiery Impose, Fiery Compose, Fiery Impose and Compose
System Accessories	Copy Control Interface Kit-A1, NFC KIT-C1, Serial Interface Kit-K3
Fax Accessories	Super G3 Fax Board-AS1, Super G3 2nd Line Fax Board-AS1, Remote Fax Kit-A1, IP FAX Expansion Kit-B1

#### Other Options

Accessibility Accessories	ADF Access Handle-A1, Voice Guidance Kit-G1, Voice Operation Kit-D1
Consumables	Staple-N1, Staple-P1, Staple Cartridge-X1, Staple Cartridge-Y1

#### For information and services contact

Canon Australia Pty Ltd	1800 444 199	canon.com.au/business
Canon New Zealand Ltd	0800 222 666	canon.co.nz/business

POWERED BY  online express

*No one does it like you*

**Canon**